


ODA

TUS.OD.001.03



Light for indoor use only

Input voltage: 110V - 60Hz

 LEDS 30W / 60W




UL 1598 ELECTRICAL INSTRUCTION FOR FLUSHMOUNTS, WALL SCONCES AND PENDANTS


SAVE THESE INSTRUCTIONS. MIN 90C SUPPLY CONDUCTORS. CAUTION-RISK OF FIRE. USE STATED WATT OR SMALLER. CAUTION-RISK OF SHOCK. DISCONNECT POWER BEFORE SERVICING. TO REDUCE THE RISK OF A BURN DURING RELAMPING, ALLOW THE BULB TO COOL DOWN. SUITABLE FOR DRY LOCATIONS ONLY. THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARD INVOLVED.

WARNING: ALL WIRES AND WIRE NUTS USED IN THE INSTALLATION MUST BE RATED 195F (90°C) FOR INDOOR USE ONLY THESE PRODUCT MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN.


1



2



3



4

